

JOANNEUM



RESEARCH



www.joanneum.at

JOANNEUM RESEARCH

Forschungsgesellschaft mbH



Assessment of Lingo-cellulosic Bioethanol Concepts in Austria – Technical, Economic and Environmental Aspects

Kurt Könighofer, Philipp Kravanja, Lorenza Canella,
Gefried Jungmeier, Anton Friedl
Wieselburg, 31.3.2011

Outline

1. Project Overview
2. Bioethanol Plant Concepts
3. Technical Data
4. Greenhouse Gas Assessment
5. Economic Analysis
6. Conclusions

Project Overview

- Title: Assessment of Lingo-cellulosic Bioethanol Concepts in Austria – Technical, Economic and Environmental Aspects
- JOANNEUM RESEARCH – RESOURCES, Research Group Energy Research
- Vienna University of Technology, Institute of Chemical Engineering, Thermal Process Engineering - Process Simulation
- Financed by Austrian Climate and Energy Fund
- Project time: 1.3.2009 - 30.4.2011



Bioethanol Plant Concepts

Key concept characteristics

- Use of C6 + C5 sugar
- Pretreatment: Steam Explosion
- Enzymatic Hydrolysis
- On-site enzyme production
- Process heat and electricity demand produced from residues (e.g. Lignin)
- Plant size (t Bioethanol per year)
 - Softwood: 50,000 / 100,000 t/y
 - Straw: 50,000 / 100,000 t/y



Concepts

Feed Stock	Fermentation of sugars	By-products	
Straw	C6	Electricity	
Straw	C6+C5	Electricity	
Straw	C6	Electricity	Heat
Straw	C6	Ligninpellets	
Straw	C6+C5	Ligninpellets	
Straw	C6	Ligninpellets	Heat
Straw	C6	C5 Molasses	Ligninpellets
Straw	C6	C5 Molasses	Heat
Straw	C6	Biomethane	Electricity
Softwood	C6	Electricity	
Softwood	C6	Ligninpellets	
Softwood	C6	Biomethane	Electricity



www.joanneum.at


Technical Data

100,000 t/y Bioethanol Concepts Overview

Feedstock		Conversion	By-products					
Type	Total Mass	Sugars in Fermentation	Bioethanol	Heat	Electricity	C5 Molasses (dry)	Lignin-pellets (dry)	Bio-methane
	kt/a		kt/a	GWh/a	GWh/a	kt/a	kt/a	GWh/a
Straw	648	C6	100		379			
	447	C5+C6	100		160			
	648	C6	100	1.003	305			
	648	C6	100				246	
	447	C5+C6	100				117	
	648	C6	100	580			191	
	648	C6	100			202	56	
	648	C6	100	551		202		
	648	C6	100		78			822
Soft-wood	867	C6	100		176			
	867	C6	100				114	
	867	C6	100		114			219


100,000 t/y Bioethanol from straw; electricity and heat (EtOH-Straw-C6/Electricity+Heat)

Straw (90%DM)	648.063 [t/y]	Straw (LHV, dry)	365,1 [MW]
SO₂	5.832 [t/y]		
NH₃ (28w/w% in H₂O)	12.970 [t/y]	Ethanol (LHV)	93,4 [MW]
Molasses (80% DM)	6.621 [t/y]	Electricity	38,1 [MW]
Corn Steep Liquor (50%DM)	19.874 [t/y]	District Heat	125,3 [MW]
Diammoniumphosphate	2.499 [t/y]		




Greenhouse Gas (GHG) Assessment


GHG flow chart: reference fossil EtOH-Straw-C6/Electricity+Heat




GHG flow chart: reference renewable EtOH-Straw-C6/Electricity+Heat



GHG Assessment 100,000 t/y EtOH-Straw-C6/Electricity+Heat



Greenhouse Gas Reduction Concepts overview



Economic Analysis

Economic Analysis Methodology

■ Costs

- Investment costs
- Insurance, maintenance
- Operating costs
 - Raw material (straw, woodchips)
 - Personal
 - Operating materials
 - Water demand
 - Waste water


■ Revenues

- Heat
- Electricity
- Ligninpellets
- C5 molasses

Economic Analysis 100,000 t/y EtOH-Straw-C6/electricity+heat

Cost Analysis		
Capital costs	[mil € / y]	26.3
Fix operating costs	[mil € / y]	11.5
Variable operating costs	[mil € / y]	61.5
of it Personal	[mil € / y]	1.8
of it Raw material	[mil € / y]	51.9
of it Operating material	[mil € / y]	6.6
Total costs	[mil € / y]	99.3
<i>Spec. total costs</i>	[€ / GJ _{Bioethanol}]	36.9
Revenues		
Electricity	[mil € / y]	15.2
Heat	[mil € / y]	20.1
Total revenues	[mil € / y]	35.3
<i>Spec. total revenues</i>	[€ / GJ _{Bioethanol}]	13.1
Total costs Bioethanol	[mil € / y]	64.0
<i>Spec.costs Bioethanol</i>	[€ / GJ _{Bioethanol}]	23.8
<i>Spec.costs Bioethanol</i>	[€ / L _{gasoline equiv.}]	0.74

Economic Analysis Concepts overview



Conclusions

Conclusions 1

- Straw and wood are interesting raw materials for lignocellulosic bioethanol in Austria
- Lignocellulosic bioethanol always in coproduction with by-products from lignin, e.g. power, heat,
- Type and amount of by-products influences technical, economic and environmental performance
- Commercial technology not available, technology under development, e.g. pilot plant for wood in Sweden, demo plant for straw in Denmark
- Priority to integration of lignocellulosic bioethanol plant in existing infrastructure, e.g. from wood in P&P-industry, from straw in EtOH from wheat plant

Conclusions 2

- GHG-reduction between 41% and 76% possible
- Costs of lignocellulosic bioethanol possible between 0,6 - 1 €/L gasoline equivalent
- Lignocellulosic bioethanol in comparison to FT-fuels: similar range of costs and environmental effects
- Further R&D necessary, e.g. in Austrian demo plant

Thank you for your attention!



JOANNEUM RESEARCH – RESOURCES

Kurt Könighofer, Lorenza Canella, Gerfried Jungmeier

www.joanneum.at/resources; Email: kurt.koenighofer@joanneum.at

Vienna University of Technology, Institute of Chemical Engineering, Thermal
Process Engineering - Process Simulation

Anton Friedl, Philipp Kravanja

www.thvt.at; Email: philipp.kravanja@tuwien.ac.at