

Advantages of Computer Modeling in Biofuel Production and Utilization Processes

Jerry Yuan, Dave Stropky

Process Simulations Ltd., Vancouver, Canada

Konstantin Pougatch, Martha Salcudean

University of British Columbia, Vancouver, Canada



August 24-27, 2009

IEA Bioenergy Multi Task Conference, Vancouver, Canada

Challenges in Biofuel Production and Utilization

- **Understanding the Biofuel Production Process**
- **Optimizing System and Equipment Design**
- **Scaling up the Design**
- **Understanding the Impact of Biofuel Utilization**
- **Optimizing the Utilization Process and Design**

Fundamentals of the Biofuel Processes

- **Fluid Flow: Single or Multi-phase**
- **Heat Transfer: Conduction, Convection, Radiation**
- **Chemical Reactions: Heterogeneous or Homogeneous, Endothermic or Exothermic, Catalytic or Non-catalytic**
- **Conservation: Momentum, Mass, and Energy**
- **Mathematical Modeling**

Advantages of Computer Modeling

- **Model application gives a deep understanding of the process.**
- **Parametric studies can be conducted efficiently and effectively.**
- **System and equipment design can be optimized and scaled up easily.**
- **Feasibility studies reduce risks of utilizing biofuel.**
- **Process and equipment of biofuel utilization can also be optimized.**

Modeling Applications

- **Biomass gasification in a fixed bed gasifier**
- **Biomass gasification in a fluidized bed gasifier**
- **Black liquor gasification in an entrained flow reactor**
- **Direct firing of wood syngas in lime kilns**
- **Direct firing of bark and lignin in lime kilns**
- **Direct firing of wood syngas in combustors**
- **Direct firing of wood syngas in boilers**
- **Direct firing of wood syngas in drying kilns**
- **Direct firing of wood syngas in HVAC applications**

Modeling a Fixed Bed Gasifier





- Nexterra gasification technology: fixed bed gasifier
- Biomass gasification: drying, pyrolysis, char gasification
- Blast air flow inside porous bed and syngas flow in freeboard
- Optimization of freeboard design for carryover reduction
- Capable of optimizing gasifier design and scaling up

Modeling Predictions and Validation


- **Modeling outputs include three-dimensional distributions of fuel and gas temperature, gas velocity, gas species concentration, the fuel feed rate, and the syngas composition.**
- **The model predictions of fuel feed rate, fuel temperature, and syngas composition are reasonably consistent with the measurements in a pilot gasifier.**
- **The modeling has been applied to a commercial gasifier design and provided reasonably good results.**

Modeling Multi-Phase Flow in Fluidized-Bed Gasifier




- **RENET gasification process (Rauch et al, 2004): fluidized-bed gasifier and combustor are separated**
- **Mixing and heat transfer between fuel and hot sand in gasifier**
- **Complete combustion of char and heat transfer to sand in combustor**
- **Multi-phase flow characteristics playing a critical role**


Prediction of Fuel and Sand Flow



Fuel





Sand






Fuel & Sand

Modeling a Black Liquor Gasifier



- High temperature and corrosive environment in the reactor
- Degrading of refractory lining and cracking of metallic supports and shell
- High temperature zone and liquor trajectory being helpful information


Temperatures and Liquor Trajectory






Model predictions		New Baseline (A/F=2.83)
Gas temperature at reactor exit	K	1446
	F	2143
Product gas CO	% dry, vol	2.88%
Product gas CO ₂	% dry, vol	20.47%
Product gas CH ₄	% dry, vol	0.48%
Product gas H ₂	% dry, vol	7.13%
Product gas H ₂ S	% dry, vol	0.24%
LHV of product gas	kJ/Nm ³ Dry	1298
Flow rate of green liquor	kg/s	1.135
Unburned combustible in green liquor	kg/s	0.068
	% of GL	5.98%
Maximum gas temperature in reactor	K	1622
	F	2460
Maximum refractory temperature	K	1492
	F	2226

Firing Wood Syngas in Lime Kilns

- Alternative fuels for natural gas and heavy oil
- Not a simple replacement of energy.
- Requirements for flame temperature and shape, volumetric flow of flue gas.
- Feasibility study, replacement ratio, burner design







Flame Temperature vs. Kiln Performance



	Model Predictions		
	100% Natural Gas	Syngas1	Syngas2
Product Rate	469.9 TPD	490.0 TPD	469.9 TPD
CaCO ₃ in Product (% mass)	1.04 %	10.33 %	0.01 %
CaO in Product (% mass)	84.3 %	75.7 %	85.2 %
Maximum Mud Temperature	1,706 deg F	1,672 deg F	1,828 deg F
Maximum Mud Surface Temperature	2,230 deg F	2,172 deg F	2,206 deg F
Product Temperature Into Coolers	1,288 deg F	1,505 deg F	1,628 deg F
Flue Gas Temperature	397 deg F	426 deg F	534 deg F
Flue Gas O ₂ (% vol)	2.0 %	2.0 %	2.0 %
Flue Gas Volumetric Flow Rate	30,496 SCFM*	31,768 SCFM*	35,104 SCFM*
Maximum Axial Average Gas Temperature	2,798 deg F	2,719 deg F	2,750 deg F
Kiln Shell Heat Loss	16.0 MMBtu/hr	16.6 MMBtu/hr	18.4 MMBtu/hr
Average Refractory Temperature	1,457 deg F	1,482 deg F	1,598 deg F
Average Shell Temperature	467 deg F	478 deg F	508 deg F

*Standard Conditions: 0 degC and 101325 Pa

Direct Firing Bark & Lignin in Lime Kilns



Optimizing Designs for Biofuel Firing

- **Dual burner for co-firing wood syngas with gas/oil in kilns**
- **Dual burner for co-firing solid biofuel with gas/oil in kilns**
- **Igniter for firing wood syngas in boilers**
- **Concerned issues: mixing, flame shape and temperature, flexibility for firing rate variation, instability, emissions, etc.**

Conclusions

- **Computer modeling provides an effective tool in biofuel research and development.**
- **We expect to work with biofuel producers in their process optimization and scaling up design.**
- **We expect to help biofuel users evaluate the utilization process and optimize the designs.**
- **PSL/UBC look forward to working with you in any kind of ways to make the world greener.**