

It is not the enzyme, it is the substrate;
but it is not the substrate so much as
the pretreatment method

Renata Bura, A. Berlin, R. Chandra, P. Chung, C. Hsieh,
S. Ewanick, D. Lam, W. Mabee, J. Pan, M. Tu,
and J. Saddler




Forest Products Biotechnology Group
The University of British Columbia

August 29th, 2006



Biomass resources in Canada



Variety of feedstocks at UBC

Agricultural residues

- Corn fibre
- Corn stover
- Rice straw
- Wheat straw



Hardwood residues

- Hybrid poplar
- Maple



Softwood residues

- Spruce
- Lodgepole pine
- Douglas fir




Steam explosion

- One of the most cost effective and efficient pretreatment for agricultural, hardwood and softwood residues
- 3 variables: time, temperature and pH
- Use of SO_2 as catalyst:
 - ↓ reaction time and temperature
 - ↑ enzyme accessibility to cellulose
 - ↑ recovery of hemicellulose



Pretreatment methods-steam explosion



Receiving vessel



Receiving vessel



Pretreated corn stover

Organosolv pulping

- Separation of the hemicellulose, lignin and cellulose
- Lignin as a co-product
- 4 variables: time, temperature, pH and ethanol concentration



Pretreatment methods-organosolv pulping



Pressure vessels




Rotary digester




Carmen
↓
Screening

Process flow


Organosolv pulping



Steam explosion



Research themes



Optimization of pretreatments

Low severity
↑ fermentation
yield
↓ solids
hydrolysis

Medium severity
good fermentation
yield
good solids
hydrolysis

High severity
↓ fermentation
yield
↑ solids
hydrolysis



Corn fibre: 190°C, 5 min, 3% SO₂, Bura *et al.*, 2003

Corn stover: 190°C, 5 min, 0% SO₂, Bura *et al.*, 2005

Hybrid poplar: 200°C, 5 min, 3% SO₂, Bura *et al.*, 2006

Hybrid poplar: 180°C, 60 min, 1.25% H₂SO₄, 60% E, Pan *et al.*, 2006*

BKLP: 205°C, 5 min, 4% SO₂, Ewanic *et al.*, 2006

BKLP: 180°C, 60 min, 1.25% H₂SO₄, 60% E, Pan *et al.*, 2006*

Douglas-fir: 195°C, 4.5 min, 4.5% SO₂, Boussaid *et al.*, 2000

Overall sugar recovery

Feedstock	Glucan recovery (%)	Xylan or mannan * recovery (%)
Corn stover ¹	100	98
Hybrid poplar ²	100	87
Beetle killed lodgepole pine ³	100	80*

¹Bura *et al.*, 2006

²Bura *et al.*, 2006

³Ewanic *et al.*, 2006



Fermentability of water soluble stream

Feedstock	Total fermentable sugars (g/L)	Relative ethanol yield (%)
Corn stover ¹	28	100
Corn fibre ²	35	95
Hybrid Poplar ³	32	75
Beetle killed lodgepole pine ⁴	30	75

¹Bura *et al.*, 2006

²Bura *et al.*, 2004


³Bura *et al.*, 2006

⁴Ewanic *et al.*, 2006



Hydrolysis of solids-2% (w/v) a.c buffer



Steam explosion, 20FPU/g of cellulose, IU:FPU 2:1



Xylan-with the solid or liquid stream?


Pretreatment	Glucan (%)	Xylan (%)
190°C, 5 min, 0% SO ₂	56	18
190°C, 5 min, 3% SO ₂	57	10

Corn stover, hydrolysis, 8% (w/v), 10FPU/g of cellulose, IU:FPU 2:1




High consistency hydrolysis

Lodgepole pine, SE-20FPU/g of cellulose, IU:FPU 2:1, organosolv- 10FPU/g of cellulose



High consistency SHF



Summary

- UBC can tailor the pretreatment and substrate characteristics to industry specifications
- The characteristics of pretreated substrates influence the performance of hydrolysis and fermentation
- SO₂ catalysed steam explosion works well with:
 - Agricultural residues (corn fibre, corn stover)
 - Hardwood residues (poplar, maple)
 - Softwood residues (lodgepole pine, spruce)
- Organosolv pulping
 - Extensive fractionation of cellulose, hemicellulose and lignin
 - The use of co-products (lignin) in the future biorefinery
 - High consistency hydrolysis and SSF



Acknowledgements

- Natural Resources Canada
- Dr. B. Cruickshank
- CAFI, USDA, NREL, Novozymes, Genencor Inc.
- Tembec Ltd.
- Forest Products Biotechnology group members



